



**Optimal performance in
rugged conditions**

BMP41 Label Printer

Optimal performance in rugged conditions

Reliable for your most detailed work and rugged enough to use every day, the BMP41 Label Printer is a must-have for DataCom and electrical professionals. Create and print labels on the spot with its QWERTY keypad or in batches at the office with Brady Workstation software. This printer can help you power through work faster, with its programmed pre-set label options for wire marking, flagging and patch panel ID.



Top applications



DataCom

Self-lam, flag labels, patch-panel, face plate labelling



Electrical

Sleeves, self-lam, wire wraps, cable markers, flag and raised panel



Wire and cable

Sleeves, self-lam, wire wraps, flag labels, cable markers



General identification

Directional marking, equipment labelling

Unique features

- Create labels quicker using a QWERTY keypad or USB connected with Brady Workstation label creation software
- Easy-to-use on-board menu options for seven different label formats, serialisation, fonts and text orientation and the ability to store 288 label files up to 48MB
- 440 on-board symbols and code 128 and 39 barcodes for various applications
- Window on printer lets you view 110+ different installed label cartridges
- 12 label material types for multiple applications in continuous and die-cut options with label widths up to 25.4 mm (1.0 inch)

Label output

- Speed: Prints up to 250 labels / day at 33.0 mm (1.3 inches) per second
- Quality: 300 dpi print resolution

Optional accessories

- Attachable magnet for hands-free label creation
- Rechargeable NiMH battery
- Hard and soft carrying cases to protect your label printer and keep accessories organised
- Quick charger

Large window on cover-door shows installed cartridge

Withstands 1.2 m drops for added jobsite durability

Popular rotating self-laminating vinyl, shrink sleeves, wire wraps, BradyGrip print-on hook material and indoor/outdoor vinyl are offered in enclosed cartridges

Simple all-in-one, drop-in cartridges for quick and easy supply change and automatic label setup

Large graphical LCD display with backlight to see exactly what you're printing

Quick-key options for wire marking, flags, patch panels that are ideal for datacom and electrical professionals

Textured rubber overmolding for better grip

QWERTY style keypad and hot keys for easier typing and reducing errors



Rechargeable battery for long lasting power supply

Sample of the easy-to-use menu keys:

Label Type

- General
- Wire Marker
- Flags
- Terminal Blog
- Patch Panel
- 66-block
- DesiStrip

Symbols

- Arrows
- Datacom
- Electrical
- International
- Fire
- Mandatory
- Exit
- First Aid
- CLP/GHS
- Greek
- HSID
- Packaging
- PPE
- Prohibition
- Safety
- Warning

Material overview

Voice & datacom identification



Electrical identification




Facility & safety identification



Material overview


| Material | Finish | Temp (°C) (Tested for 30 days) | | Additional Features | Application | Approval/Compliance |
|--------------------------------------|------------|-----------------------------------|----------|---|---|---|
| | | Min. | Max. | | | |
| Heat-shrink Polyolefin Sleeve | | | | | | |
| B-342 | Matt | -55 °C | 130.6 °C | Heat-shrinkable; Self-Extinguishing. Available in White or Yellow. | Wire & cable labelling | UL Recognised to UL224; SAE-AMS-DTL-23053/5 C (Class 1); SAE-AS-81531 |
| Metallised Polyester | | | | | | |
| B-428 | Matt | -70 °C | 120 °C | Designed for rating or serial plates, product information, warranty labels and inventory control labels. | Circuit board labelling Component & equipment labelling General identification Inventory & inspection labelling | UL Recognised; CSA Accepted; Halogen Free (DIN VDE 0472/part 815) |
| Nylon Cloth | | | | | | |
| B-499 | Matt | -40 °C | 90 °C | Permanent adhesion; write-on capabilities. Available in White. | Electrical labelling General identification Laboratory labelling | UL Recognised; CSA Accepted; Halogen Free (DIN VDE 0472/part 815) Approvals are for White material only |
| Polyester | | | | | | |
| B-414 | Matt | -40 °C | 50 °C | Get a grip on your wire and cable identification – Brady and VELCRO® Brand have partnered to bring you BradyGrip™ Print-on Hook Material, an exclusive print-and-place material that can be easily applied, repositioned or removed. | Wire & cable labelling | |
| B-422 | Gloss | -40 °C | 100 °C | 2 mil adhesive recommended for application on textured surfaces. | Barcode labelling Circuit board labelling Component & equipment labelling Data & telecom labelling Electrical labelling General identification Inventory & inspection labelling | UL Recognised; CSA Accepted |
| B-483A | Gloss | -40 °C | 120 °C | Ultra-aggressive adhesive; Designed for powder coated surfaces. Available in Black, Blue, Green, Orange, Red, White and Yellow. | Barcode labelling Component & equipment labelling Data & telecom labelling Electrical labelling General identification Inventory & inspection labelling | UL Recognised; CSA Accepted |
| Polypropylene Tag | | | | | | |
| B-412 | Matt | -40 °C | 100 °C | Highly durable labels, ideal for wire & cable identification or product inventory identification, where legibility & tensile strength are needed. Available in White. | Data & telecom labelling | |
| Reflective Tape | | | | | | |
| B-584 | Gloss | -40 °C | 70 °C | Suitable for outdoor use. Available in White and Yellow. | Component & equipment labelling General identification | |
| Self-laminating Vinyl | | | | | | |
| B-427 | Matt | -40 °C | 60 °C | Self-laminating; Self-extinguishing; Excellent water & oil resistance; Excellent abrasion and smudge resistance. Available in White/Transparent, Yellow/Transparent and Rotating Label version (includes a non-adhesive printable zone and a translucent, self-adhesive laminate that is wrapped around a cable). | Electrical labelling Wire & cable labelling | UL Recognised to UL969 Labelling and Marking Standard when printed with the Brady Series R4300 and R6200 ribbons. See UL files MH17154 for specific details. Brady customers should specify at purchase if they require UL Recognised B-427 labels. Brady sells both UL Recognised B-427 labels and non-approved labels depending on customer requirements. |
| Vinyl | | | | | | |
| B-595 | Gloss | -40 °C | 82 °C | Available in a wide range of colours. | Facility identification Laboratory labelling | BS5609:1986 Section 2 and section 3 |
| Vinyl Cloth | | | | | | |
| B-498 | Semi-gloss | -40 °C | 80 °C | Removable from flat surfaces; write-on capabilities. Available in White. | Laboratory labelling Wire & cable labelling | UL Recognised |



Router, server, faceplate, outlet and patch panel labels

Create the labels you need in one easy process. Create a fully-formatted serialised punch block label to fit your equipment or label your ports, jacks and outlets with adhesive labels or slide-in strips.

- Developed to withstand abrasion and low temperatures
- Designed to withstand exposure to numerous solvents
- High adhesion to textured metals, powder coated surfaces and low surface energy plastics



| Diagram | Order Reference | Colour | Label Width A (mm) | Label Height B (mm) | Label Length B (m) | Labels per Roll | Additional Features |
|-----------------------------|------------------|-----------------|--------------------|---------------------|--------------------|-----------------|--|
| B-412: Polypropylene | | | | | | | |
| ⊙ | MC-375-412 | Black on White | 9.53 | – | 6.10 m | 1 | Non-Adhesive Slide-in Strips |
| ⊙ | MC-475-412 | Black on White | 12.07 | – | 6.10 m | 1 | Non-Adhesive Slide-in Strips |
| ⊙ | MC-625-412 | Black on White | 15.88 | – | 6.10 m | 1 | Non-Adhesive Slide-in Strips |
| B-422: Polyester | | | | | | | |
| ⊙ | MC-375-422 | Black on White | 9.53 | – | 7.62 m | 1 | Adhesive Stick-on Strips: Outlet, Patch Panel, Cont. Tape, Cut to Size |
| ⊙ | MC-475-422 | Black on White | 12.07 | – | 7.62 m | 1 | Adhesive Stick-on Strips: Outlet, Patch Panel, Cont. Tape, Cut to Size |
| ▲ | M-7-422 | Black on White | 12.70 | 12.70 | – | 280 | Port Labels |
| ⊙ | MC-500-422 | Black on White | 12.70 | – | 7.62 m | 1 | Adhesive Stick-on Strips: Outlet, Patch Panel, Cont. Tape, Cut to Size |
| ⊙ | MC-625-422 | Black on White | 15.88 | – | 7.62 m | 1 | Adhesive Stick-on Strips: Outlet, Patch Panel, Cont. Tape, Cut to Size |
| ▲ | M-47-422 | Black on White | 25.40 | 12.70 | – | 480 | Stick-on Individual Labels |
| B-483A: Polyester | | | | | | | |
| ▲ | M-47-483 | Black on White | 25.40 | 12.70 | – | 480 | Ultra-aggressive adhesive; Designed for powder coated surfaces |
| B-595: Vinyl | | | | | | | |
| ⊙ | MC-500-595-YL-BK | Black on Yellow | 12.70 | – | 7.62 m | 1 | Adhesive Stick on Strips, Cut to Size |
| ⊙ | MC-500-595-CL-WT | White on Clear | 12.70 | – | 6.10 m | 1 | Adhesive Stick on Strips, Cut to Size |
| ⊙ | MC-750-595-YL-BK | Black on Yellow | 19.05 | – | 7.62 m | 1 | Adhesive Stick on Strips, Cut to Size |
| ⊙ | MC-750-595-CL-WT | White on Clear | 19.05 | – | 6.10 m | 1 | Adhesive Stick on Strips, Cut to Size |



How to read an order reference: example M-31-427-YL


M - **31** - **427** - **YL**
M: Die-cut label **Label size code** **Brady material** **Optional colour**
MC: Continuous label **number (B-number)**



Closets, racks, frames and blocks labels

Durable materials, easy to slide in or stick on providing clearly legible identification to guarantee swift routine and non-routine maintenance as well as emergency repairs to keep the infrastructure running smoothly.

- Flexible with high-tack adhesives for easy and long-lasting adhesion
- Various sizes in several durable materials
- Rating plate labels offer a metal looking finish




| Diagram | Order Reference | Colour | Label Width A (mm) | Label Height B (mm) | Label Length B (m) | Labels per Roll | Additional Features |
|------------------------------------|--------------------|-----------------|--------------------|---------------------|--------------------|-----------------|--|
| B-422: Polyester | | | | | | | |
| ▲ | M-89-422 | Black on White | 12.70 | 38.10 | – | 180 | Stick-on Individual Labels |
| ▲ | M-47-422 | Black on White | 25.40 | 12.70 | – | 480 | Stick-on Individual Labels |
| ⊙ | MC1-1000-422 | Black on White | 25.40 | – | 7.62 m | 1 | Adhesive Stick-on Strips: Outlet, Patch Panel, Cont. Tape, Cut to Size |
| ▲ | M-49-422 | Black on White | 25.40 | 25.40 | – | 260 | Adhesive Stick-on individual labels |
| ▲ | M-90-422 | Black on White | 38.10 | 19.05 | – | 180 | Stick-on Individual Labels |
| B-428: Metallised Polyester | | | | | | | |
| ◐ | M-92-428-BB | Black on Silver | 12.70 | 33.02 | – | 239 | Rating & Nameplate labelling with a metal looking finish |
| ▲ | M-60-428 | Black on Silver | 50.80 | 25.40 | – | 140 | Rating & Nameplate labelling with a metal looking finish |
| B-483A: Polyester | | | | | | | |
| ▲ | M-60-483 | Black on White | 50.80 | 25.40 | – | 140 | Ultra-aggressive adhesive; Designed for powder coated surfaces |
| ▲ | M-61-483 | Black on White | 50.80 | 12.70 | – | 80 | Ultra-aggressive adhesive; Designed for powder coated surfaces |
| B-595: Vinyl | | | | | | | |
| ⊙ | MC1-1000-595-YL-BK | Black on Yellow | 25.40 | – | 7.62 m | 1 | Adhesive Stick on Strips, Cut to Size |
| ⊙ | MC1-1000-595-CL-WT | White on Clear | 25.40 | – | 6.10 m | 1 | Adhesive Stick on Strips, Cut to Size |

For additional general purpose tapes, see Indoor/Outdoor Grade Facility and Safety Labels on page 14.



Equipment, inside panel component, air conditioning & power gear labelling


Operational efficiency is also crucial in the datacenters' grey spaces in order to guarantee qualitative data availability and transfer. Clear identification may relieve the burden for data center maintenance or repair technicians in an effective way.




| Diagram | Order Reference | Colour | Label Width A (mm) | Label Height B (mm) | Label Length B (m) | Labels per Roll | Additional Features |
|------------------------------------|--------------------|-----------------|--------------------|---------------------|--------------------|-----------------|--|
| B-422: Polyester | | | | | | | |
| ⊙ | MC1-1000-422 | Black on White | 25.40 | – | 7.62 m | 1 | Adhesive Stick-on Strips: Outlet, Patch Panel, Cont. Tape, Cut to Size |
| ▲ | M-49-422 | Black on White | 25.40 | 25.40 | – | 260 | Adhesive Stick-on individual labels |
| ▲ | M-90-422 | Black on White | 38.10 | 19.05 | – | 180 | Stick-on Individual Labels |
| B-428: Metallised Polyester | | | | | | | |
| ☾ | M-92-428-BB | Black on Silver | 12.70 | 33.02 | – | 239 | Rating & Nameplate labelling with a metal looking finish |
| ▲ | M-47-428 | Black on Silver | 25.40 | 12.70 | – | 480 | Rating & Nameplate labelling with a metal looking finish |
| ▲ | M-60-428 | Black on Silver | 50.80 | 25.40 | – | 140 | Rating & Nameplate labelling with a metal looking finish |
| B-595: Vinyl | | | | | | | |
| ⊙ | MC1-1000-595-YL-BK | Black on Yellow | 25.40 | – | 7.62 m | 1 | Adhesive Stick on Strips, Cut to Size |
| ⊙ | MC1-1000-595-OR-BK | Black on Orange | 25.40 | – | 7.62 m | 1 | Adhesive Stick on Strips, Cut to Size |
| ⊙ | MC1-1000-595-BL-WT | White on Blue | 25.40 | – | 7.62 m | 1 | Adhesive Stick on Strips, Cut to Size |
| ⊙ | MC1-1000-595-RD-WT | White on Red | 25.40 | – | 7.62 m | 1 | Adhesive Stick on Strips, Cut to Size |
| ⊙ | MC1-1000-595-GN-WT | White on Green | 25.40 | – | 7.62 m | 1 | Adhesive Stick on Strips, Cut to Size |


Outdoor towers, roadside cabinets and underground chambers labels

Improve visibility in low-light and inclement weather conditions with this reflective material.



| Diagram | Order Reference | Colour | Label Width A (mm) | Label Length B (m) | Additional Features |
|-------------------------------|-----------------|-----------------|--------------------|--------------------|---------------------------|
| B-584: Reflective Tape | | | | | |
| ⊙ | MC-500-584 | Black on White | 12.70 | 6.10 m | Suitable for outdoor use. |
| ⊙ | MC-500-584-YL | Black on Yellow | 12.70 | 6.10 m | Suitable for outdoor use. |
| ⊙ | MC-750-584 | Black on White | 19.05 | 6.10 m | Suitable for outdoor use. |
| ⊙ | MC-750-584-YL | Black on Yellow | 19.05 | 6.10 m | Suitable for outdoor use. |






Self-laminating wire & cable markers

Self-laminating markers feature a printable zone in white or yellow and a transparent, non printable area that wraps around wires and cables and serves as an overlamine to the printed text.

- Designed to adhere to highly curved surfaces, wires and cables
- Superior resistance to abrasion, handling, solvents, water, oil, dirt and more




| Diagram | Order Reference | Colour | Label Width A (mm) | Label Height B (mm) | Label Length B (m) | Printable Area Width PW (mm) | Printable Area Height PH (mm) | Labels per Roll | Max. Wire Diameter (mm) | For Data Cables Sized to Fit |
|------------------------------|-----------------|-----------------------------|--------------------|---------------------|--------------------|------------------------------|-------------------------------|-----------------|-------------------------|--|
| B-427: Self-laminating Vinyl | | | | | | | | | | |
| ▶ | M-53-427 | Black on White/Transparent | 101.60 | 25.40 | – | 25.40 | 25.40 | 70 | 24.30 | 50 Pair Copper; 24 Pair Fibre; Backbone |
| ▶ | M-53-427-YL | Black on Yellow/Transparent | 101.60 | 25.40 | – | 25.40 | 25.40 | 70 | 24.30 | 50 Pair Copper; 24 Pair Fibre; Backbone |
| ▶ | M-89-427 | Black on White/Transparent | 12.70 | 12.70 | – | 12.70 | 12.70 | 180 | 8.10 | CAT 6; 4 pair UTP Copper |
| ▶ | M-11-427 | Black on White/Transparent | 12.70 | 19.05 | – | 12.70 | 9.53 | 360 | 3.00 | |
| ▶ | M-102-427 | Black on White/Transparent | 12.70 | 31.75 | – | 12.70 | 9.53 | 200 | 7.10 | CAT 6; 4 pair UTP Copper |
| ▲ | MC-750-427 | Black on White/Transparent | 19.05 | – | 7.62 m | 9.53 | – | 1 | 3.00 | CAT 6; 4 pair UTP Copper |
| ▶ | M-90-427 | Black on White/Transparent | 19.05 | 38.10 | – | 19.05 | 12.70 | 180 | 8.10 | CAT 6; 4 pair UTP Copper |
| ▶ | M-47-427 | Black on White/Transparent | 25.40 | 12.70 | – | 12.70 | 9.53 | 360 | 5.10 | 2 Pair Fibre/Coaxial, Single/Multi-Mode |
| ▶ | M-136-427 | Black on White/Transparent | 25.40 | 19.05 | – | 25.40 | 9.53 | 340 | 3.00 | |
| ▶ | M-48-427 | Black on White/Transparent | 25.40 | 19.05 | – | 9.53 | 19.05 | 200 | 3.00 | CAT 6; 4 pair UTP Copper |
| ▶ | M-49-427 | Black on White/Transparent | 25.40 | 25.40 | – | 25.40 | 9.53 | 260 | 5.10 | 2 Pair Fibre/Coaxial; Single/Multi-Mode |
| ▶ | M-143-427 | Black on White/Transparent | 25.40 | 31.75 | – | 25.40 | 12.70 | 200 | 6.10 | CAT 6; 4 pair UTP Copper |
| ▶ | M-31-427 | Black on White/Transparent | 25.40 | 38.10 | – | 25.40 | 12.70 | 180 | 8.10 | CAT 6; 4 pair UTP Copper |
| ▶ | M-91-427-YL | Black on Yellow/Transparent | 25.40 | 38.10 | – | 25.40 | 12.70 | 180 | 8.10 | CAT 6; 4 pair UTP Copper |
| ▶ | M-51-427 | Black on White/Transparent | 25.40 | 63.50 | – | 25.40 | 19.05 | 110 | 14.20 | 25 pair Copper; 4-12 pair Fibre; Coaxial |
| ▶ | M-51-427-YL | Black on Yellow/Transparent | 25.40 | 63.50 | – | 25.40 | 19.05 | 110 | 14.20 | 25 pair Copper; 4-12 pair Fibre; Coaxial |



Rotating self-laminating wire & cable markers

The B-427 self-laminating Rotating Label can be rotated around a cable thanks to a non-adhesive printable zone and a translucent, self-adhesive laminate that is wrapped around a cable.

- Faster cable identification thanks to a label that can be rotated around a cable to make its print visible from any angle
- Industrial grade label that stays attached and remains legible on cables and components
- Spins freely around your Cat 5 and fiber optic cables, no adhesive residue or label parts to cling to your wires




| Diagram | Order Reference | Colour | Label Width A (mm) | Label Height B (mm) | Printable Area Width PW (mm) | Printable Area Height PH (mm) | Labels per Roll | Max. Wire Diameter (mm) |
|------------------------------|-----------------|-------------------|--------------------|---------------------|------------------------------|-------------------------------|-----------------|-------------------------|
| B-427: Self-laminating Vinyl | | | | | | | | |
| RO | M-206-RO-427 | White/Transparent | 12.70 | 62.23 | 12.70 | 17.78 | 75 | 5.13 |
| RO | M-207-RO-427 | White/Transparent | 12.70 | 97.79 | 12.70 | 27.94 | 50 | 8.07 |
| RO | M-211-RO-427 | White/Transparent | 25.40 | 43.18 | 25.40 | 12.70 | 100 | 3.65 |
| RO | M-203-RO-427 | White/Transparent | 25.40 | 62.23 | 25.40 | 17.78 | 75 | 5.13 |
| RO | M-209-RO-427 | White/Transparent | 25.40 | 97.79 | 25.40 | 27.94 | 50 | 8.07 |



Cable flags

The flag wizard allows to create a flag label that perfectly wraps around a wire or cable, with the ends joined together to form a flag.



| Diagram | Order Reference | Colour | Label Width A (mm) | Label Height B (mm) | Printable Area Height PH (mm) | Labels per Roll | Additional Features |
|--------------------|-----------------|----------------|--------------------|---------------------|-------------------------------|-----------------|--|
| B-499: Nylon Cloth | | | | | | | |
| ☆ | M-141-499 | Black on White | 25.40 | 57.15 | 25.40 | 90 | |
| B-483A: Polyester | | | | | | | |
| ▲ | M-60-483 | Black on White | 50.80 | 25.40 | – | 140 | Ultra-aggressive adhesive; Designed for powder coated surfaces |
| ▲ | M-47-483 | Black on White | 25.40 | 12.70 | – | 480 | Ultra-aggressive adhesive; Designed for powder coated surfaces |
| ▲ | M-61-483 | Black on White | 50.80 | 12.70 | – | 80 | Ultra-aggressive adhesive; Designed for powder coated surfaces |
| B-499: Nylon Cloth | | | | | | | |
| ⊙ | MC-375-499 | Black on White | 9.53 | – | – | 1 | |
| ⊙ | MC-500-499 | Black on White | 12.70 | – | – | 1 | |
| ⊙ | MC-750-499 | Black on White | 19.05 | – | – | 1 | |





BradyGrip™ print-on hook material

BradyGrip™ Print-on Hook Material is a one-of-a-kind solution that allows identification to be easily printed and placed on bundles. A grippy backing makes it easy to reposition or remove, so no need for costly rework. Just print on and place - it's that simple.

- Maximises your uptime with faster, printable ID for cable bundles.
- Apply, reposition and remove with exclusive, print-and-place material.
- Offers a non-damaging alternative to nylon cable ties.
- Customise labels to fit big or small jobs by printing on different-width material.

| Diagram | Order Reference | Colour | Label Width A (mm) | Label Length B (m) | Recommended Velcro® One-Wrap® size range to use with BradyGrip™ (mm) |
|------------------|-----------------|----------------|--------------------|--------------------|--|
| B-414: Polyester | | | | | |
| ⊙ | MC-250-414 | Black on White | 6.35 | 3.66 m | 6.35 - 13.0 |
| ⊙ | MC-500-414 | Black on White | 12.70 | 3.66 m | 12.7 - 16.0 |
| ⊙ | MC-750-414 | Black on White | 19.05 | 3.66 m | 19.05 - 50.0 |






Terminal block markers

Specially designed markers that offer a highly unique adhesive and vinyl cloth construction for excellent holding power, while still allowing for clean removal and application.

- Specially designed narrow-width continuous label for alignment on terminal blocks and patch panels
- Software can auto-serialise these labels to help save you time


| Diagram | Order Reference | Colour | Label Width A (mm) | Label Length B (m) |
|--------------------|-----------------|----------------|--------------------|--------------------|
| B-498: Vinyl Cloth | | | | |
| | MC-240-498 | Black on White | 6.10 | 4.88 m |
| | MC-318-498 | Black on White | 8.08 | 4.88 m |
| | MC-375-498 | Black on White | 9.53 | 6.10 m |



PermaSleeve PS Wire Marking Sleeves

These heat-shrink sleeves are the ultimate in marker durability, permanence and aesthetic appearance. Fast shrink rate saves time and costs during installation. Meets SAE-AMS-DTL-23053/5C (class 1), SAE-AS-81531, MIL-STD-202, and tested per ASTM E162, ASTM E662.

- 3:1 heat-shrink sleeve that fits snugly around wires
- Fade-resistant and flame-retardant
- Available as individual die-cut markers or continuous cut-to-length tubing




| Diagram | Order Reference | Colour | Sleeve Width A (mm) | Sleeve Height B (mm) | Sleeve Length B (m) | Min. Wire Diameter (mm) | Max. Wire Diameter (mm) | Sleeves per Roll |
|-------------------------------|-----------------|-----------------|---------------------|----------------------|---------------------|-------------------------|-------------------------|------------------|
| B-342: Heat-shrink Polyolefin | | | | | | | | |
| | M-125-075-342 | Black on White | 19.05 | 6.00 | — | 1.17 | 2.79 | 80 |
| | M-187-075-342 | Black on White | 19.05 | 8.50 | — | 1.57 | 3.81 | 80 |
| | M-250-075-342 | Black on White | 19.05 | 11.15 | — | 2.39 | 5.46 | 80 |
| | M-375-075-342 | Black on White | 19.05 | 16.40 | — | 3.18 | 8.13 | 80 |
| | MC-125-342-YL | Black on Yellow | — | 5.97 | 2.13 m | 1.17 | 2.79 | 1 |
| | MC-125-342 | Black on White | — | 6.00 | 2.13 m | 1.17 | 2.79 | 1 |
| | MC-187-342 | Black on White | — | 8.50 | 2.13 m | 1.57 | 3.81 | 1 |
| | MC-187-342-YL | Black on Yellow | — | 8.50 | 2.13 m | 1.57 | 3.81 | 1 |
| | MC-250-342 | Black on White | — | 11.15 | 2.13 m | 2.39 | 5.46 | 1 |
| | MC-375-342 | Black on White | — | 16.40 | 2.13 m | 3.18 | 8.13 | 1 |
| | MC-250-342-YL | Black on Yellow | — | 11.15 | 2.13 m | 2.39 | 5.46 | 1 |



Magnet Accessory Available

The BMP41 Label Printer offers a heavy-duty magnet accessory that allows you to go hands free. Apply the magnet to the back of your printer and then simply place on a magnetic surface.






Wrap Around Wire & Cable Markers

Durable vinyl cloth wrap around wire and cable markers made with an adhesive that allows the markers to be removed cleanly and re-applied if necessary.


- Highly unique adhesive and cloth construction
- Ideal choice for marking both ends of a wire that may need be cut shorter before final termination

| Diagram | Order Reference | Colour | Label Width A (mm) | Label Height B (mm) | Max. Wire Diameter (mm) | Labels per Roll |
|--------------------|-----------------|----------------|--------------------|---------------------|-------------------------|-----------------|
| B-498: Vinyl Cloth | | | | | | |
| ▲ | M-7-498 | Black on White | 12.70 | 12.70 | 2.80 | 240 |
| ▲ | M-48-498 | Black on White | 19.05 | 25.40 | 5.10 | 180 |
| ▲ | M-11-498 | Black on White | 19.05 | 12.70 | 4.00 | 220 |
| ▲ | M-91-498 | Black on White | 25.40 | 38.10 | 7.10 | 120 |
| ▲ | M-49-498 | Black on White | 25.40 | 25.40 | 5.10 | 160 |
| ▲ | M-131-498 | Black on White | 12.70 | 25.40 | 5.10 | 180 |




Control Panel and Electrical Panel Labels

Long-lasting, durable materials to quickly identify control and electrical panels.




| Diagram | Order Reference | Colour | Label Width A (mm) | Label Height B (mm) | Label Length B (m) | Labels per Roll |
|-----------------------------|-----------------|-----------------|--------------------|---------------------|--------------------|-----------------|
| B-422: Polyester | | | | | | |
| ⊙ | MC-625-422 | Black on White | 15.88 | — | 7.62 m | 1 |
| B-428: Metallised Polyester | | | | | | |
| ▲ | M-47-428 | Black on Silver | 25.40 | 12.70 | — | 480 |
| ▲ | M-60-428 | Black on Silver | 50.80 | 25.40 | — | 140 |



Automation & Electrical Component Markers

Various sizes, colours and label types for marking relays, solenoids, switches, drive motors, and other components.




| Diagram | Order Reference | Colour | Label Width A (mm) | Label Height B (mm) | Label Length B (m) | Labels per Roll |
|------------------------------------|--------------------|-----------------|--------------------|---------------------|--------------------|-----------------|
| B-422: Polyester | | | | | | |
| ▲ | M-89-422 | Black on White | 12.70 | 38.10 | – | 180 |
| ▲ | M-7-422 | Black on White | 12.70 | 12.70 | – | 280 |
| ⊙ | MC-500-422 | Black on White | 12.70 | – | 7.62 m | 1 |
| ▲ | M-47-422 | Black on White | 25.40 | 12.70 | – | 480 |
| ⊙ | MC1-1000-422 | Black on White | 25.40 | – | 7.62 m | 1 |
| ▲ | M-49-422 | Black on White | 25.40 | 25.40 | – | 260 |
| ▲ | M-90-422 | Black on White | 38.10 | 19.05 | – | 180 |
| B-428: Metallised Polyester | | | | | | |
| ☾ | M-92-428-BB | Black on Silver | 12.70 | 33.02 | – | 239 |
| ▲ | M-47-428 | Black on Silver | 25.40 | 12.70 | – | 480 |
| ▲ | M-60-428 | Black on Silver | 50.80 | 25.40 | – | 140 |
| B-483A: Polyester | | | | | | |
| ▲ | M-47-483 | Black on White | 25.40 | 12.70 | – | 480 |
| ▲ | 131599 | Black on White | 50.80 | 25.40 | – | 140 |
| ▲ | M-61-483 | Black on White | 50.80 | 12.70 | – | 80 |
| B-499: Nylon Cloth | | | | | | |
| ▲ | M-130-499 | Black on White | 9.53 | 20.96 | – | 220 |
| ⊙ | MC-375-499 | Black on White | 9.53 | – | 4.88 m | 1 |
| ▲ | M-131-499 | Black on White | 12.70 | 25.40 | – | 180 |
| ⊙ | MC-500-499 | Black on White | 12.70 | – | 4.88 m | 1 |
| ▲ | M-11-499 | Black on White | 12.70 | 19.05 | – | 220 |
| ⊙ | MC-750-499 | Black on White | 19.05 | – | 4.88 m | 1 |
| ▲ | M-128-499 | Black on White | 25.40 | 48.26 | – | 100 |
| B-595: Vinyl | | | | | | |
| ⊙ | MC-500-595-OR-BK | Black on Orange | 12.70 | – | 7.62 m | 1 |
| ⊙ | MC-750-595-OR-BK | Black on Orange | 19.05 | – | 7.62 m | 1 |
| ⊙ | MC1-1000-595-OR-BK | Black on Orange | 25.40 | – | 7.62 m | 1 |
| ⊙ | MC-500-595-YL-BK | Black on Yellow | 12.70 | – | 7.62 m | 1 |
| ⊙ | MC-750-595-YL-BK | Black on Yellow | 19.05 | – | 7.62 m | 1 |
| ⊙ | MC1-1000-595-YL-BK | Black on Yellow | 25.40 | – | 7.62 m | 1 |




Self-laminating Wire & Cable Markers

Self-laminating markers feature a printable zone in white or yellow and a transparent, non printable area that wraps around wires and cables and serves as an overlamine to the printed text.

- Designed to adhere to highly curved surfaces, wires and cables
- Superior resistance to abrasion, handling, solvents, water, oil, dirt and more




| Diagram | Order Reference | Colour | Label Width A (mm) | Label Height B (mm) | Label Length B (m) | Printable Area Width PW (mm) | Printable Area Height PH (mm) | Max. Wire Diameter (mm) | Labels per Roll |
|-------------------------------------|-----------------|-----------------------------|--------------------|---------------------|--------------------|------------------------------|-------------------------------|-------------------------|-----------------|
| B-427: Self-laminating Vinyl | | | | | | | | | |
| Ⓛ | M-89-427 | Black on White/Transparent | 12.70 | 12.70 | – | 12.70 | 12.70 | 8.10 | 180 |
| Ⓛ | M-11-427 | Black on White/Transparent | 12.70 | 19.05 | – | 12.70 | 9.53 | 3.00 | 360 |
| Ⓛ | M-90-427 | Black on White/Transparent | 19.05 | 38.10 | – | 19.05 | 12.70 | 8.10 | 180 |
| Ⓛ | MC-750-427 | Black on White/Transparent | 19.05 | – | 7.62 m | 9.53 | – | 3.00 | 1 |
| Ⓛ | M-47-427 | Black on White/Transparent | 25.40 | 12.70 | – | 12.70 | 9.53 | 5.10 | 360 |
| Ⓛ | M-136-427 | Black on White/Transparent | 25.40 | 19.05 | – | 25.40 | 9.53 | 3.00 | 340 |
| Ⓛ | M-48-427 | Black on White/Transparent | 25.40 | 19.05 | – | 9.53 | 19.05 | 3.00 | 200 |
| Ⓛ | M-49-427 | Black on White/Transparent | 25.40 | 25.40 | – | 25.40 | 9.53 | 5.10 | 260 |
| Ⓛ | M-143-427 | Black on White/Transparent | 25.40 | 31.75 | – | 25.40 | 12.70 | 6.10 | 200 |
| Ⓛ | M-31-427 | Black on White/Transparent | 25.40 | 38.10 | – | 25.40 | 12.70 | 8.10 | 180 |
| Ⓛ | M-91-427-YL | Black on Yellow/Transparent | 25.40 | 38.10 | – | 25.40 | 12.70 | 8.10 | 180 |
| Ⓛ | M-51-427 | Black on White/Transparent | 25.40 | 63.50 | – | 25.40 | 19.05 | 14.20 | 110 |
| Ⓛ | M-51-427-YL | Black on Yellow/Transparent | 25.40 | 63.50 | – | 25.40 | 19.05 | 14.20 | 110 |
| Ⓛ | M-53-427 | Black on White/Transparent | 101.60 | 25.40 | – | 25.40 | 25.40 | 24.30 | 70 |
| Ⓛ | M-53-427-YL | Black on Yellow/Transparent | 101.60 | 25.40 | – | 25.40 | 25.40 | 24.30 | 70 |
| Ⓛ | M-102-427 | Black on White/Transparent | 12.70 | 31.75 | – | 12.70 | 9.53 | 7.10 | 200 |



Rotating self-laminating wire & cable markers

The B-427 self-laminating Rotating Label can be rotated around a cable thanks to a non-adhesive printable zone and a translucent, self-adhesive laminate that is wrapped around a cable.

- Faster cable identification thanks to a label that can be rotated around a cable to make its print visible from any angle
- Industrial grade label that stays attached and remains legible on cables and components




| Diagram | Order Reference | Colour | Label Width A (mm) | Label Height B (mm) | Printable Area Width PW (mm) | Printable Area Height PH (mm) | Max. Wire Diameter (mm) | Labels per Roll |
|-------------------------------------|-----------------|-------------------|--------------------|---------------------|------------------------------|-------------------------------|-------------------------|-----------------|
| B-427: Self-laminating Vinyl | | | | | | | | |
| Ⓛ | M-206-RO-427 | White/Transparent | 12.70 | 62.23 | 12.70 | 17.78 | 5.13 | 75 |
| Ⓛ | M-207-RO-427 | White/Transparent | 12.70 | 97.79 | 12.70 | 27.94 | 8.07 | 50 |
| Ⓛ | M-211-RO-427 | White/Transparent | 25.40 | 43.18 | 25.40 | 12.70 | 3.65 | 100 |
| Ⓛ | M-203-RO-427 | White/Transparent | 25.40 | 62.23 | 25.40 | 17.78 | 5.13 | 75 |
| Ⓛ | M-209-RO-427 | White/Transparent | 25.40 | 97.79 | 25.40 | 27.94 | 8.07 | 50 |



Bin, storage, reflective and general industrial labels

Choose from several materials and types of labels that offer an aggressive adhesive for use in commercial and industrial applications. Bin, storage & industrial labels are ideal for commercial / industrial applications, while reflective can be used for low light or inclement weather conditions.

- Recommended for low surface energy and textured surfaces
- Reflective is ideal for outdoor utility poles and pedestals, equipment on site and rooftop equipment



| Diagram | Order Reference | Colour | Label Width A (mm) | Label Height B (mm) | Label Length B (m) | Labels per Roll |
|--------------------------|-----------------|----------------|--------------------|---------------------|--------------------|-----------------|
| B-422: Polyester | | | | | | |
| ⊙ | MC-375-422 | Black on White | 9.53 | – | 7.62 m | 1 |
| ⊙ | MC-475-422 | Black on White | 12.07 | – | 7.62 m | 1 |
| ▲ | M-7-422 | Black on White | 12.70 | 12.70 | | 280 |
| ▲ | M-89-422 | Black on White | 12.70 | 38.10 | | 180 |
| ⊙ | MC-500-422 | Black on White | 12.70 | – | 7.62 m | 1 |
| ▲ | M-47-422 | Black on White | 25.40 | 12.70 | | 480 |
| ▲ | M-49-422 | Black on White | 25.40 | 25.40 | | 260 |
| ⊙ | MC1-1000-422 | Black on White | 25.40 | – | 7.62 m | 1 |
| ▲ | M-90-422 | Black on White | 38.10 | 19.05 | | 180 |
| B-483A: Polyester | | | | | | |
| ▲ | M-47-483 | Black on White | 25.40 | 12.70 | | 480 |
| ▲ | M-61-483 | Black on White | 50.80 | 12.70 | | 80 |
| ▲ | 131599 | Black on White | 50.80 | 25.40 | | 140 |


| Diagram | Order Reference | Colour | Label Width A (mm) | Label Height B (mm) | Label Length B (m) | Labels per Roll |
|-------------------------------|--------------------|-----------------|--------------------|---------------------|--------------------|-----------------|
| B-499: Nylon Cloth | | | | | | |
| ▲ | M-11-499 | Black on White | 12.70 | 19.05 | | 220 |
| ▲ | M-128-499 | Black on White | 25.40 | 48.26 | | 100 |
| B-584: Reflective Tape | | | | | | |
| ⊙ | MC-500-584 | Black on White | 12.70 | – | 6.10 m | 1 |
| ⊙ | MC-500-584-YL | Black on Yellow | 12.70 | – | 6.10 m | 1 |
| ⊙ | MC-750-584 | Black on White | 19.05 | – | 6.10 m | 1 |
| ⊙ | MC-750-584-YL | Black on Yellow | 19.05 | – | 6.10 m | 1 |
| B-595: Vinyl | | | | | | |
| ⊙ | MC-500-595-RD-WT | White on Red | 12.70 | – | 7.62 m | 1 |
| ⊙ | MC-750-595-RD-WT | White on Red | 19.05 | – | 7.62 m | 1 |
| ⊙ | MC1-1000-595-RD-WT | White on Red | 25.40 | – | 7.62 m | 1 |



Indoor/Outdoor Grade Facility & Safety Labels

Pliable vinyl that conforms well to smooth or rough surfaces such as pipes, walls, doors, panels, shelving, bins and equipment. Lasting up to 8-10* years outdoors, these labels offer excellent resistance to oils, detergents, dirt, grime and many solvents.

- Durable, low-shrink vinyl with our most aggressive adhesive
- Works for a variety of applications, including 5S labels, pipe markers, arc flash, chemical labels and more



| Diagram | Order Reference | Colour | Label Width A (mm) | Label Length B (m) | Labels per Roll |
|---------------------|--------------------|-----------------|--------------------|--------------------|-----------------|
| B-595: Vinyl | | | | | |
| ⊙ | MC-500-595-CL-BK | Black on Clear | 12.70 | 6.10 m | 1 |
| ⊙ | MC-750-595-CL-BK | Black on Clear | 19.05 | 6.10 m | 1 |
| ⊙ | MC1-1000-595-CL-BK | Black on Clear | 25.40 | 6.10 m | 1 |
| ⊙ | MC-500-595-OR-BK | Black on Orange | 12.70 | 7.62 m | 1 |
| ⊙ | MC-750-595-OR-BK | Black on Orange | 19.05 | 7.62 m | 1 |
| ⊙ | MC1-1000-595-OR-BK | Black on Orange | 25.40 | 7.62 m | 1 |
| ⊙ | MC-500-595-WT-BK | Black on White | 12.70 | 7.62 m | 1 |
| ⊙ | MC-750-595-WT-BK | Black on White | 19.05 | 7.62 m | 1 |
| ⊙ | MC1-1000-595-WT-BK | Black on White | 25.40 | 7.62 m | 1 |
| ⊙ | MC-500-595-YL-BK | Black on Yellow | 12.70 | 7.62 m | 1 |
| ⊙ | MC-750-595-YL-BK | Black on Yellow | 19.05 | 7.62 m | 1 |
| ⊙ | MC1-1000-595-YL-BK | Black on Yellow | 25.40 | 7.62 m | 1 |
| ⊙ | MC-500-595-WT-RD | Red on White | 12.70 | 7.62 m | 1 |
| ⊙ | MC-750-595-WT-RD | Red on White | 19.05 | 7.62 m | 1 |
| ⊙ | MC1-1000-595-WT-RD | Red on White | 25.40 | 7.62 m | 1 |

| Diagram | Order Reference | Colour | Label Width A (mm) | Label Length B (m) | Labels per Roll |
|---------------------|--------------------|----------------|--------------------|--------------------|-----------------|
| B-595: Vinyl | | | | | |
| ⊙ | MC-500-595-BK-WT | White on Black | 12.70 | 7.62 m | 1 |
| ⊙ | MC-750-595-BK-WT | White on Black | 19.05 | 7.62 m | 1 |
| ⊙ | MC1-1000-595-BK-WT | White on Black | 25.40 | 7.62 m | 1 |
| ⊙ | MC-500-595-BL-WT | White on Blue | 12.70 | 7.62 m | 1 |
| ⊙ | MC-750-595-BL-WT | White on Blue | 19.05 | 7.62 m | 1 |
| ⊙ | MC1-1000-595-BL-WT | White on Blue | 25.40 | 7.62 m | 1 |
| ⊙ | MC-500-595-CL-WT | White on Clear | 12.70 | 6.10 m | 1 |
| ⊙ | MC-750-595-CL-WT | White on Clear | 19.05 | 6.10 m | 1 |
| ⊙ | MC1-1000-595-CL-WT | White on Clear | 25.40 | 6.10 m | 1 |
| ⊙ | MC-500-595-GN-WT | White on Green | 12.70 | 7.62 m | 1 |
| ⊙ | MC-750-595-GN-WT | White on Green | 19.05 | 7.62 m | 1 |
| ⊙ | MC1-1000-595-GN-WT | White on Green | 25.40 | 7.62 m | 1 |
| ⊙ | MC-500-595-RD-WT | White on Red | 12.70 | 7.62 m | 1 |
| ⊙ | MC-750-595-RD-WT | White on Red | 19.05 | 7.62 m | 1 |
| ⊙ | MC1-1000-595-RD-WT | White on Red | 25.40 | 7.62 m | 1 |

* Average expected outdoor life of product will depend on user definition of failure, climatic conditions, mounting techniques and material colour. The 8 to 10 year outdoor durability applies to the vinyl label stock only; ribbon durability will vary. A polyester overlaminate is recommended for harsh environments - long term exposure to wind and rain.

Printer part numbers

| Article No. | Order Reference | Description |
|-------------|-----------------|--|
| 133254 | BMP41-KIT-EU | BMP41 Label Printer - EU |
| 198648 | BMP41-EU-PWID | BMP41 Label Printer - EU with Brady Workstation PWID Suite |
| 711213 | BMP41-KIT-UK | BMP41 Label Printer - UK |
| 198629 | BMP41-UK-PWID | BMP41 Label Printer - UK with Brady Workstation PWID Suite |



The Basic Suite is included with every printer, all you need to do is download it. Workstation.BradyID.com/Free



Quickly identify your products and wires with customised text or graphical labels, using serialised or imported data. Workstation.BradyID.com/ProductandWire

Printer technical data

The BMP41 Label Printer is reliable for your most detailed work and rugged enough to use every day, it's a must-have for datacom and electrical professionals.

Create and print labels on-the-spot with its QWERTY keypad, or in batches at the office with Brady Workstation software.

This printer can help you power through work faster with its programmed pre-set label options for wire marking, flagging and patch panel ID.

The BMP41 is ready for it all, every day.

| Specifications | |
|---|--|
| Print Technology | Thermal Transfer |
| Print Resolution (dpi) | 300 dpi |
| Print Speed (mm/sec) | 33.00 mm/s |
| Colour Capability | Monocolour |
| Continuous vs Die-cut Labels | Continuous and Die-cut |
| Max. Label Width (mm) | 25.40 mm |
| Max. Print Length | 7620.00 mm |
| Recommended Usage per Day | 250 |
| Stand-alone Printing (Detached from PC) | Stand-alone & Peripheral |
| Connectivity Options | USB |
| PC Connectivity | Yes |
| Bar Code Type | Code 39 and 128, other via software |
| Built-in Symbols | 480 |
| Software Compatibility | Brady Workstation CodeSoft |
| Physical Properties | |
| Size - W x H x D (mm) | 152.40 x 292.00 x 89.00 |
| Weight (kg) | 1.29 kg |
| Keyboard Type | QWERTY |
| Display | LCD |
| Cutter | Single Hand Manual Actuate Straight Cut |
| Warranty | 2 years |



Easily store your portable printer, some consumables and a number of accessories in a lightweight soft bag with protective padding that keeps your identification tools neatly together.



2 YEAR WARRANTY

Electrical kit

| Article No. | Order Reference | Description |
|-------------|-----------------|---|
| 198650 | BMP41-EU-ELEC | BMP41 Label Printer - Electrical Kit - EU |
| 198652 | BMP41-UK-ELEC | BMP41 Label Printer - Electrical Kit - UK |

Kit includes one of each

| | |
|--|---|
| BMP41 Label Printer - EU or BMP41 Label Printer - UK | |
| BMP41-HC | BMP41 Hard Case |
| BMP41-MAGNET | BMP41 Magnet |
| BWS PWID Suite | Brady Workstation PWID Suite |
| M-91-427 | Black on White/Transparent Self-laminating Vinyl, 25.40 mm x 38.10 mm, 180 labels / Cartridge |
| MC1-1000-595-WT-BK | Black on White Vinyl, 25.40 mm x 7.62 m, 1 / Cartridge |
| M-131-499 | Black on White Nylon Cloth, 12.70 mm x 25.40 mm, 180 labels / Cartridge |

Voice & datacom kit

| Article No. | Order Reference | Description |
|-------------|-----------------|--|
| 198649 | BMP41-EU-DATA | BMP41 Label Printer - Voice & Datacom Kit - EU |
| 198651 | BMP41-UK-DATA | BMP41 Label Printer - Voice & Datacom Kit - UK |

Kit includes one of each

| | |
|--|---|
| BMP41 Label Printer - EU or BMP41 Label Printer - UK | |
| BMP41-HC | BMP41 Hard Case |
| BMP41-MAGNET | BMP41 Magnet |
| BWS PWID Suite | Brady Workstation PWID Suite |
| M-48-427 | Black on White/Transparent Self-laminating Vinyl, 25.40 mm x 19.05 mm, 200 labels / Cartridge |
| MC1-1000-595-WT-BK | Black on White Vinyl, 25.40 mm x 7.62 m, 1 / Cartridge |
| MC-375-422 | Black on White Polyester, 9.53 mm x 7.62 m, 1 / Cartridge |

BMP41 Accessories

| Article No. | Order Reference | Description |
|-------------|-----------------|---|
| 114883 | M-AC-143110 | AC Adaptor, USA 120V |
| 133255 | BMP41-BATT | Rechargeable Nickel Metalhydride battery for the BMP41 and BMP61 printers |
| 133257 | BMP41-HC | BMP41 Hard Case |
| 134176 | BMP41-MAGNET | BMP41 Magnet |
| 143114 | USB-CABLE | BMP41-BMP50 Series USB Cable |
| 150618 | BMP-SC-2 | Protective softbag for portable printers - BMP41/BMP61 |
| 710612 | M50-71-AC-BC-EU | AC Adaptor, Europe 220V |
| 710613 | M50-71-AC-BC-UK | AC Adaptor, UK 240V |
| 711222 | BMP41-QC-EU | EU External Battery Quick Charger for BMP41 and BMP61 |
| 711223 | BMP41-QC-UK | UK External Battery Quick Charger for BMP41 and BMP61 |

Africa

Randburg, South Africa
 Tel.: +27 11 704 3295
 Email: africa@bradycorp.com

Benelux

Zele, Belgium
 Tel.: +32 (0) 52 45 78 11
 Email: benelux@bradycorp.com

Central & Eastern Europe

Bratislava, Slovakia
 Tel.: +421 2 3300 4800
 Email: central_europe@bradycorp.com

Denmark

Odense
 Tel.: +45 66 14 44 00
 Email: denmark@bradycorp.com

France

Roncq
 Tel.: +33 (0) 3 20 76 94 48
 Email: france@bradycorp.com

Germany, Austria & Switzerland

Egelsbach, Germany
 Tel.: +49 (0) 6103 7598 660
 Email: germany@bradycorp.com

Hungary

Budaörs
 Tel.: +36 23 500 275
 Email: central_europe@bradycorp.com

Italy

Gorgonzola
 Tel.: +39 02 26 00 00 22
 Email: italy@bradycorp.com

Middle East FZE

Dubai, UAE
 Tel.: +971 4881 2524
 Email: me@bradycorp.com

Norway

Kjeller
 Tel.: +47 70 13 40 00
 Email: norway@bradycorp.com

Russia

Moscow
 Tel.: +7 495 269 47 87
 Email: central_europe@bradycorp.com

Spain & Portugal

Madrid, Spain
 Tel.: +34 900 902 993
 Email: spain@bradycorp.com,
 portugal@bradycorp.com

Sweden, Finland, Baltic states

Kista, Sweden
 Tel.: +46 (0) 8 590 057 30
 Email: sweden@bradyeurope.com

Turkey

Istanbul
 Tel.: +90 212 264 02 20 / 264 02 21
 Email: turkey@bradycorp.com

UK & Ireland

Banbury, UK
 Tel.: +44 (0) 1295 228 288
 Email: uk@bradycorp.com

Our mission is to identify and protect people, products and premises



To help minimise our impact on the environment, Brady limits its number of reprints.

Updated versions are always available for download on www.bradyeurope.com.

 Search for: EUR-M-427-EN



Y3292019

Your distributor

10/02/2021