

PDU Technology Specification

Date: 05/06/2022

NO.: SWDT0312205002

Customer	Direktronik	RoHS	Yes
Product Name	Designated Power Distribution Unit for Cabinet	Customer's Code	
Part Number	190-3891	Picture Code	SWDT0312205002
No.	Item	Detailed Description	
1	Product Series	AUE2211	
2	Socket Type	Iec 320 C19 standard, press (right)[2];Double IEC320 C13 Socket[8]; Blue color	
3	Socket Quantity	18	
4	Power Input	Left end single input	
5	Bracket Install	Inverse installation	
6	Cable with plug	IEC60309 plug (32A 2P+E)	
7	Control Function	No controlling function	
8	Protection Function	LED display digital ammeter[1];	
9	Case	Black	
10	Cable Specification	3 x 6.0 mm ² x 3M	
11	Product Size	L x W x H = 874 x 56 x 44.4 mm	
12	Mounting Length	853 mm	
13	Case Length	821 mm	
14	PDU Exponent	0.881	
15	Fittings	2pcs $\phi 6 \times 16$ mm cross bolt, 2pcs M6 float nut,	
16	Product Label	Product Name	Designated Power Distribution Unit for Cabinet
		Specification Model	190-3891
		Rating voltage	250VAC 50/60Hz
		Rating Current	32A
		Max. Current	
		Max. Power	8000W
		Safety Authentication	CE
		Logo	RoHS
		Producer	
No.	Add-In		
1	Socket assemble	No	
2	Interior Connection Wire	2.5 mm ² (14AWG)	
3	Interior Connection Style	Standard connection	
4	Fix the Cable	Cable clamp(19)	
5	Module Assemble (from left to right)	Pls refer to the drawing	

Preview



IEC60309 plug (32A 2P+E)

DIMENSION AND TOLERANCES (Unit: mm)				
Length:	874	Mounting length:	853	
Width:	56	Case length:	821	Customer
Height:	44.4	case tolerance:	± 1.0	Product name
				Part number
DRAWN	Linda	DATE	05/06/2022	Customer's code
CHK'D				Drawing number
APP'D				Edition number