



## Specification

**Part Number** 20116972

### Input

Nominal Voltage	230V
Frequency	50Hz
Phase	Single phase
Plug type	IEC60309 (32A 230VAC 2P+E) / Legrand
Power Cord Spec	3 x 6.0mm <sup>2</sup> x 3 meters
Max input current	32A
Rated input current	32A
Wiring Style	L-N wiring
Power Capacity	7.36kW

### Output

Nominal Voltage	230V
Max output current	32A
Output Connections	21 x IEC 320 C13; 3 x IEC 320 C19
Outlet Locking	Only available with C13

### Protections

Circuit Overload Protection	2 x 16A hydraulic circuit breakers; single pole
Surge Suppression	None

### Metering & switching

Input/phase/circuit Metering	Yes
Outlet Metering	Yes
Breaker Status Monitoring	Yes
Metering Accuracy	+/- 1%
Outlet Switching	No
Environmental Monitoring	Temperature, Humidity, (Door contact, Water leakage, Smoke status customizable with external sensor box)
Monitoring Parameters	Voltage (V), Current (A), Active Power (kW), Real Power (kVA), Energy (kWh), Power Factor, Breaker status

### Communication

Access	SNMP (V1,V2c,V3) , Http/Https, Telnet, Modbus-RTU
Authentication	N/A
Alerts	Voltage, current, (temperature, humidity ,door status ,water leaking ,smoke) optional
Service	TFTP,SMTP
Daisy-chain	1 master 3 slaves

### Physical

Product Dimensions (HxWxD)	1829 x 56 x 52mm
Box Dimensions (HxWxD)	TBD
Product Weight	9kg
Box Weight	10kg
Mounting Style	Rear button mounting
Mounting Distance	1556mm


### Environmental

Operating Temperature -10~45°C  
Operating Relative Humidity 5%~95%  
Operating Elevation 0~3000 meters

### Compliance

EMC Verification EN55022, EN61000  
Safety Verification IEC/EN 60950, IEC/EN 62368  
Environmental Verification RoHS 2.0

## Drawing



# DIREKTRONIK

Direktronik AB tel. 08-52 400 700 [www.direktronik.se](http://www.direktronik.se)