

20117376 RG 11 A/U Marine SHF1

75 Ω
SHF1
DNV / ABS


Application

Coaxial cable designed for ship- and offshore applications with excellent EMC properties. Data and video signals transmission. Electrical data in compliance with MIL C-17/F.



Construction

Conductor	Stranded Tinned Cu 7 x 0.40 [mm]
Dielectricum	Low density PE 7.25 \pm 0.18 [mm]
Screen	Al + polyester + Al tape
Screen 2	Cu- braid 96 [% optical coverage]
Jacket	Black SHF1
O.D.	10.3 \pm 0.18 [mm]
Weight	150 [kg/km]



Specifications

Operating temperature normal	-30 – 70 [°C]
Test Voltage	5.5 [kV]
Characteristic impedance	75 \pm 3 Ω
Braid Resistance	4.4 [Ω /km]
Conductor resistance	20.5 [Ω /km]
Capacitance	67 [pF/km]
Velocity factor	0.67
Min. bending radius	5 [x outer diam]
Min. bending radius flexible	10 [x outer diam]



SE

Direktronik AB | Box 234 , 149 23 Nynäshamn | Besöksadress Konsul Johnsons väg 15 149 45 Nynäshamn
Telefon 08 52 400 700 | Fax | Epost info@direktronik.se | Org.nr 556281-9663 | Bankgiro 922-0179



NO

NEXLAN AS | Kokstadflaten 19 B, 5257 Kokstad | Besöksadresse Kokstadflaten 19 B 5257 Kokstad
Telefon 55 50 91 50 | Fax | E-post info@direktronik.no | Org.nr 986767215MVA | Bankgiro 36285556559

Norms

Halogenfree, max content corrosive and toxic gases	IEC 60754-1 & IEC 60754-2
Design and testing standards	IEC 60096-0-1 Ed 3
Flame resistance	IEC 60332-3-22 Cat.A
Flame retardant	IEC 60332-1
Toxic gases max.	NES 713 CEI 20-37/7
Weather resistant	ASTM G 154
Smoke emission	IEC 61034-2
Oil and fuel resistant	IEC 60811
Water immersion	IEC 60502
UV-resistant	UL 1581, ISO 4892 ASTM D 2565 92A
Certification	DNV / ABS



Alternative designs, armoured, MUD resistant, in any combination.

Attenuation nominal, max 105%

Frequency MHz	Attenuation dB/100m
5	1.1
10	1.3
50	4.2
100	6.1
300	11.8
500	16
800	21.4
1000	24.3
1500	31
1750	36
2150	40.2
2500	42.4
3000	49



SE

Direktronik AB | Box 234, 149 23 Nynäshamn | Besöksadress Konsul Johnsons väg 15 149 45 Nynäshamn
Telefon 08 52 400 700 | Fax | Epost info@direktronik.se | Org.nr 556281-9663 | Bankgiro 922-0179



NO

NEXLAN AS | Kokstadflaten 19 B, 5257 Kokstad | Besøksadresse Kokstadflaten 19 B 5257 Kokstad
Telefon 55 50 91 50 | Fax | E-post info@direktronik.no | Org.nr 986767215MVA | Bankgiro 36285556559

Structural return loss

MHz	dB
30 – 300	>30
300 – 600	>27
600 – 1000	>25
1000 – 2000	>22
2000 – 3000	>20

Screen effectiveness IEC 61196-1

MHz	dB
100 – 900	>90
900 – 2000	>80
2000 – 3000	>70



Direktronik AB | Box 234, 149 23 Nynäshamn | Besöksadress Konsul Johnsons väg 15 149 45 Nynäshamn
 Telefon 08 52 400 700 | Fax | Epost info@direktronik.se | Org.nr 556281-9663 | Bankgiro 922-0179

SE



NEXLAN AS | Kokstadflaten 19 B, 5257 Kokstad | Besöksadresse Kokstadflaten 19 B 5257 Kokstad
 Telefon 55 50 91 50 | Fax | E-post info@direktronik.no | Org.nr 986767215MVA | Bankgiro 36285556559

NO