

DIREKTRONIK

Dataprodukter utöver det vanliga



Standard equipment in strong plastic case
current source 230V/10A or 115V/20A



Pull line blower EZ50

The simple way to

blow or

vacuum pull line.

Facts

- **Blow** or vacuum pull line **without compressor** (ø 1 mm, tensile strength 24 kg)
- For all commercially available cable **conduits** (internal diameter from ø 18 to 50 mm)
- For cable installations in private, business and industrial buildings
- Appropriate for flexible conduits/innerducts
- **Trouble shooter** for blocked conduits
- Huge **time saving** in cable feeding on longer distances
- Lightweight and compact
- Excellent accessibility, even in confined spaces
- Easy to handle
- Suitable in any car boot
- Perfect value for money



EZ50 Video



Pull line blower EZ50 for electrical installations

Intended Use:

- insert a special **pull line** in all commercial **conduits (int. ø 18 to 50 mm)**
- installations in the range of private houses, office and industrial buildings
- for all commercial boxes, junction boxes, sockets, lamp boxes etc. (even in very confined spaces)
- problems with e.g. kinked conduits can be solved by switching to suction mode, sucking the pull line from opposite end

Function:

- apply line brake
- fit joint/nozzle appropriate to internal conduit diameter
- firstly, blow through the conduit with air, check if penetrable tube/correct tube
- make either a loop or fix a bead to the pull line
- release line brake
- blow pull line in without interrupting, observe uncoiling in cylinder
- release switch and close nozzle with a finger
- apply line brake and cut off pull line
- fix wire/s to the pull line and start pulling

EZ50 Pull line blower

Standard equipment in strong plastic case

- 1 Pull line blower EZ50
- 2 pull line rolls ø 1 mm, approx. 900 m, tensile strength approx. 24 kg
- 1 suction device
- Components set A: 2 joints ½", reduction 19/12 mm and nozzle int. ø 9,5 mm
- Components set B: 3 joints ¾", nozzle int. ø 16 mm plus nozzle int. ø 19 mm
- 1 special nozzle black, for internal diameter from 25 to 50 mm
- 1 special nozzle with 90° angle, external diameter 12 mm (only in connection with special nozzle black)
- 3 beads of ø 11, 13 and 16 mm each
- Operating instructions

*Also available as **EZ50 + PLUS** version with the marked additional accessories.

Special Accessories (please order separately):

- Parachute for ducts ø 30-60 mm*
- Spray nozzle for lubricants*
- Shuttle sets for optimal pull line transport through the conduit (ø 20-50 mm)*

