

Best.nr: 20101907, 20101908, 20101909

Fiber-optic Video Format Converters

DATA SHEET

Contents

- ◆ **Description**
- 1) **Key Features**
- 2) **Applications**
- 3) **Technical Specifications**
- 4) **Absolute Maximum Ratings**
- 5) **Operating Conditions**
- 6) **Recommended Specifications of Fiber-Optic Cable**
- 7) **Functions**
- 8) **Drawing**
- 9) **Connection Diagram**

Fiber-optic Video Format Converters

Description

Opticis provides high-end fiber-optic video format converters such as multi-format converter, OMVC-200 and single-format converters, DVDF-200, VGDF-200, SVDF-200 and CNDF-200 to manipulate from old fashioned to leading-edge video formats in a various video system applications. Both two (2) types of converter handle DVI, VGA, Component video, S-video and Composite video as an input and convert these signals to 1-fiber DVI. All signals can be transmitted up to 500m (1,640ft) using 50 μ m multi-mode fiber at WUXGA (1920x1200) or 1080p, 60Hz. Especially, multi-format converter, OMVC-200 automatically detects the first incoming signal among various signals or decides a priority input by pre-programming as DVI, VGA, Component, Composite and S-Video in an order when all signals are connected and turned on.

The latest multi/single-format converters support all VESA resolutions up to WUXGA (1920x1200) at 60Hz, up to 1080p at 60Hz for Component and 480i, 576i for Composite and S-Video executing this SD signal input, NTSC/PAL (480i, 576i) to SXGA (1280x1024). The others are remained as same resolution.

The OMVC-200 can be mountable up to two (2) units and four (4) units for single-format converters in 19" 1RU rack and both two (2) types of converter installed in various places such as, a back side of display or frame by two (2) types of mounting bracket complying with VESA 75, 100 standards. The EDID in a display can be read and restored by just pressing EDID button in a front panel of OMVC-200, DVDF-200 and VGDF-200. This EDID programming feature makes the installation more easy and flexible at any variable resolution of display systems. The LED indicators are equipped for Power-on and Status (signal transmission and EDID learning for DVI and VGA) on a front panel.

Opticis converters are used for long haul video applications and special place where the optimal signal quality and electrical isolation are required and our own 1-fiber DVI receiver, DVFX-100-R is used as a pair to execute optical to electrical DVI conversion.

The line-up is composed of

- 1) Multi-format converter, OMVC-200 Best.nr: 20101906
- 2) DVI to 1-fiber DVI converter, DVDF-200 Best.nr: 20101909
- 3) VGA to 1-fiber DVI converter, VGDF-200 Best.nr: 20101907
- 4)
- 5) S-video / Composite video to 1-fiber DVI, SVDF-200 Best.nr: 20101908

All converters are constituted of three (3) parts as follows;

- One (1) Converter unit
- One (1) 5V/3A, AC/DC power adaptor with locking type outlet (Medical grade of certification)
- Two (2) types of mounting bracket (Optional);
 - 1) Type A has female screw holes to be fixed from the outside where there are VESA standard bare holes.
 - 2) Type B has a bare hole to fix from the inside to outside where three are VEAS standard female screw holes.

1. Fiber-optic Video Format Converters

1) Key Features

- Supports all VESA resolution up to WUXGA (1920x1200) at 60Hz for DVI and VGA,
up to 1080p, 60Hz for Component video,
480i and 576i for Composite video and S-Video
- Automatically detects the first incoming signal among various video sources and converts it into one (1) optical DVI output with SC termination (OMVC-200, SVDF-200)
- Be scale-up 480i and 576i to SXGA (1280x1024) for S-Video/Composite video inputs (OMVC-200, SVDF-200).
- Except the case above, it maintains input and output resolutions.
- Transmits up to 500m using 50 μ m multi-mode fiber at WUXGA or 1080p, 60Hz
- 2 units or 4 units can be mountable in 19" 1RU rack (OMVC-200, Single-format converters)
- Provides mounting bracket complying with VESA 75, 100 standards to be attached on various places (Optional – OMVC-200, Single-format converters)
- Includes one (1) +5V DC 3A power adapter (Medical grade of certification)
- Certifications: CE / FCC, Laser Safety - DVDF-200, VGDF-200. CE / FCC – OMVC-200

2) Applications

- Medical equipment
- Control room
- Conference room / Education
- Various application requiring long haul video applications and special place where the optimal signal quality and electrical isolation are needed

3) Technical Specifications

i) General Specifications (OMVC-200, DVDF/VGDF/SVDF/CNDF-200)

	Parameter	Specifications
Electrical	Input Signal Type	DVI: TMDS VGA: RGBHV, RGsB, RGBS Composite & S-Video: NTSC/PAL Component: YPbPr
	Input Connectors	DVI: 24pin DVI-I VGA: HD15, D-sub Component: 3 x RCA S-video: Mini-DIN Composite: RCA

	Supporting Resolution	DVI & VGA: VGA to WUXGA (1920 x 1200), 60Hz Component: 480i to 1080p, 60Hz S-video & Composite: Up-scale 480i and 576i to SXGA (1280x1024), 60Hz
	Power Consumption	OMVC-200, DVDF-200 < 6W, VGDF/SVDF/CNDF-200 <5W
	Max. Bit rate	Max. 1.65Gbps
Optical	Output Optical Connector	SC
	Laser Diodes in Output	Multi-mode VCSEL (Vertical Cavity Surface Emitting Laser)
	Output Optical Power	< 1 dBm
Mechanical	Dimension (WDH)	Multi-format: 216 x 112 x 44mm
		Single-format: 104 x 112 x 28mm
Fiber	Optical Connector	Simplex SC connectors
	Recommended Fiber	50/125 μ m Multi-mode Glass Fiber

4) Absolute Maximum Ratings (OMVC-200, DVDF/VGDF/SVDF/CNDF-200)

Parameter	Symbol	Minimum	Maximum	Units
Supply Voltage	V _{CC}	-	+ 6.0	V
Operating Temperature	T _{op}	0	50	°C
Storage Temperature	T _s	- 30	+ 70	°C
Storage Relative Humidity	H _s	10	95	%RH

5) Operating Conditions

i) DVI Input (OMVC-200, DVDF-200)

	Parameter	Symbol	Minimum	Typical	Maximum	Units
Power Supply	Supply Voltage	V _{CC}	-	5.0	5.5	V
	Supply Current	I _{TCC}	-	1110	1200	mA
	Power Dissipation	P _{TX}	-	5.55	6.6	W
	Power Supply Rejection (Note1)	PSR		50		mV _{p-p}
TMDS	Data Input Load	R _{LD}		50		Ω
	Graphic Supply Voltage (Note2)	GV _{CC}	+ 3.1	+ 3.3	+ 3.5	V
	Single-Ended High Level Input Voltage	GV _{IH}	GV _{CC} - 0.01	GV _{CC}	GV _{CC} + 0.01	V
	Single-Ended Low Level Input Voltage	GV _{IL}	GV _{CC} - 0.6	-	GV _{CC} - 0.4	V
	Single-Ended Input Swing Voltage	GV _{ISWING}	0.4	-	0.6	V
	Resolution range	-	640x480	-	1920x1200	-

Note1. Tested with a 50mV_{p-p} sinusoidal signal in the frequency range from 500 Hz to 500 MHz on the VCC supply with the recommended power supply filter in place. Typically less than a 0.25 dB change in sensitivity is experienced.

Note2. Graphic Supply Voltage is regulated reference voltage for signal processing in modules.

ii) VGA Input (OMVC-200, VGDF-200)

	Parameter	Symbol	Minimum	Typical	Maximum	Units
Power Supply	Supply Voltage	V _{CC}	-	5.0	5.5	V
	Supply Current	I _{TCC}	-	890	950	mA
	Power Dissipation	P _{TX}	-	4.45	5.22	W
	Power Supply Rejection	PSR		50		mV _{p-p}
Video Input	Data Output Load	R _{LD}		75		Ω
	Input Signal Level	RGB		0.7		V _{p-p}
	Horizontal Frequency	HF	30	-	91	KHz
	Vertical Frequency	VH	50	-	85	KHz
	Resolution range (Note3)	-	640x480	-	1920x1200	-

Note3. Only the reduced blanking version of the 1920x1200 resolution is sampled at full bit rate.

iii) Component Input (OMVC-200, CNDF-200)

	Parameter	Symbol	Minimum	Typical	Maximum	Units
Power Supply	Supply Voltage	V _{CC}	-	5.0	5.5	V
	Supply Current	I _{TCC}	-	810	850	mA
	Power Dissipation	P _{TX}	-	4.05	4.68	W
	Power Supply Rejection	PSR		50		mV _{p-p}
Video Input	Data Input Load	R _{LD}		75		Ω
	Input Signal Level	Y		1		V _{p-p}
		PbPr		0.7		V _{p-p}
	Resolution range	-	480i@60	-	1080p@60	-

iv) S-Video/Composite Input (OMVC-200, SVDF-200)

	Parameter	Symbol	Minimum	Typical	Maximum	Units
Power Supply	Supply Voltage	V _{CC}	-	5.0	5.5	V
	Supply Current	I _{TCC}	-	850	900	mA
	Power Dissipation	P _{TX}	-	4.25	4.95	W
	Power Supply Rejection	PSR		50		mV _{p-p}
Video Input	Data Input Load	R _{LD}		75		Ω
	Resolution range (Note4)	-		NTSC, PAL		

Note4. Output Resolution: 1280x1024@60Hz

v) Optical DVI Output (OMVC-200, DVDF/VGDF/SVDF/CNDF-200)

	Parameter	Symbol	Minimum	Typical	Maximum	Units
Optical Output	Output Optical Power	P _o			1	dBm
	Wavelength	λ	850		990	nm
	Spectral width in RMS	Δλ			3	nm
	Relative Intensity of Noise	RIN		-20		dB/Hz
	Extinction Ratio	Ext	4			dB
	Rising/Falling Time	T _{rise} /T _{fall}			260	ps
	Jitter in p-p value	T _{jitter}			260	ps

6) Recommended Specifications of Fiber-Optic Cable

Parameters	Conditions	Specifications
Fiber Type		50μm Multi-mode Graded Index Glass Fiber
Modal Bandwidth	λ = 850nm	Min. 500 MHz km
Fiber Cable Attenuation	λ = 850nm	Max. 2.5dB/km
Extension Distance		10 – 1,640ft (500 meters)
No. of Ferrules	SC	1 ferrule
Skew		Max. 0.4ns
Insertion Attenuation		Max. 0.5dB
Total Optical Attenuation	In 330 ft (100 meter) extension	Max. 1.5dB

7) Functions

i) Self-EDID Function (DVI and VGA)

The EDID in a display can be read and restored by just pressing EDID button on front panel. This Self-EDID programming feature makes the installation of OMVC-200 more easy and flexible at any variable resolution display systems.

ii) Auto Signal Detection

It automatically detects the first incoming signal among various signals or decides a priority by pre-programming in an order of DVI, VGA, Component, Composite and S-Video when all signals are connected at the same time.



iii) Upscale NTSC/PAL to SXGA

It also executes an upscale NTSC/PAL (480i, 576i) to SXGA (1280x1024) for S-Video/Composite video input. The others are remained as same resolution.

8) Drawing Dimension [mm]



i) Multi-format converter, OMVC-200

(WDH) = 216 x 112 x 44mm



ii) Single-format converter, DVDF-200, VGDF-200, CNDF-200, SVDF-200

(WDH) = 104 x 112 x 28mm



9) Connection Diagram

The diagram shows the connection of single-format converter (VGDF-200) and 1-fiber DVI extender (Receiver; DVFX-100-RX) by one (1) SC multi-mode fiber.

