

## MINI DIGITAL CLAMP METER

# KPS-PA900 MINI



- Mini digital current clamp
- 26 mm jaw
- 6000 counts
- AC / DC voltage, AC current, resistance, frequency and duty cycle measurements
- SMART function: automatic detection of the measured parameter
- Continuity warning
- Dual screen
- Maximum and minimum values
- Hold readings on screen
- Backlit display, auto scaling, auto power off and low battery indication
- CAT.III 600V according to EN 61010



# KPS-PA900 MINI

## MINI DIGITAL CLAMP METER

General	
Power Supply	3×1.5V AAA Batteries
Product Size	204mm × 78 mm × 43mm
Product Weight	195g
Certificate	CE/ETL/RoHS
Safety Rating	CAT III 600V

Specs	
Display Counts	6000
Jaw Opening	Φ26mm/1.0"
Auto Range	✓
Auto Power Off	✓
Dual Display	✓
Continuity Buzzer	<40Ω
MAX/MIN Measurement	✓
Data Hold	✓
Display Backlight	✓
Low Battery Display	✓

# KPS-PA900 MINI

## MINI DIGITAL CLAMP METER

Specs	Range	Resolution	Accuracy
DC Voltage	6V/60V/600V	0.01V/0.1V/1V	± (0.5% + 3 digits)
AC Volatge	6V/60V/600V	0.01V/0.1V/1V	± (0.8% + 5 digits)
AC Current	2A/20A/200A	0.01V/0.1V/1V	± (2.5% + 8 digits)
	600A	1A	± (3.0% + 10 digits)
Resistance	2kΩ/20kΩ/200kΩ/2MΩ	0.001kΩ/0.01kΩ/0.1kΩ /0.001MΩ	± (0.8% + 3 digits)
	10MΩ	0.01MΩ	± (1.0% + 5 digits)
Frequency (A)	60Hz/600Hz/3kHz	0.1Hz/1Hz/10Hz	± (1.0% + 5 digits)
Frequency (V)	60Hz/600Hz/3kHz	0.1Hz/1Hz/10Hz	± (1.0% + 5 digits)
Duty Cycle	10% ÷ 90%	1%	± 2.0%

### Product Code Information

SKU	KPSPA900MINICBINT
EAN code	8435394747224
UPC code	810053670200
Pcs/export carton	20